

PART 1: GENERAL

1.01 Scope Of Standard

- A. This standard provides general guidance concerning the specific preferences of the Sam Houston State University for roofing systems.
- B. SHSU recognizes that project conditions and requirements vary, thus precluding the absolute adherence to the items identified herein in all cases. However, unless there is adequate written

SAM HOUSTON STATE UNIVERSITY
DIVISION 07 THERMAL & MOISTURE PROTECTION

3. S

3. If existing roof is mechanically fastened, determine how to remove roof and methods to repair substrate.
 - B. Test for asbestos, lead, and asphaltic substances whose removal may require abatement or special environmental considerations.
 - C. Inspect existing skylights and report to SHSU project representative whether it would be prudent to include skylight re-work with roof repairs. Likewise, for roof scuttle and other rooftop accessories.
 - D. Remove existing roof to substrate unless approved by SHSU. Never remove more roof than can be dried-in prior to completion of day's work or in the event of rain.
 - E. Provide for substrate repair/replacement in Base Bid (by assumed quantities or percentages, and unit prices, if necessary).
 - F. Replace all nailers. Provide unit prices with bid to allow existing nailers to remain if determined to be satisfactory.
 - G. Re-use of existing counter flashing is permissible if SHSU project representative agrees. Verify height of finished roof and include repair in bid.